

Parameter	Value	Unit
Initial temperature	25.0	°C
Final temperature	25.0	°C
Initial pressure	1.013	bar
Final pressure	1.013	bar
Initial volume	0.001	m³
Final volume	0.001	m³
Initial mass	0.001	kg
Final mass	0.001	kg
Initial density	1000	kg/m³
Final density	1000	kg/m³
Initial viscosity	0.001	Pa·s
Final viscosity	0.001	Pa·s
Initial thermal conductivity	0.6	W/m·K
Final thermal conductivity	0.6	W/m·K
Initial specific heat capacity	4182	J/kg·K
Final specific heat capacity	4182	J/kg·K
Initial enthalpy	4182	J/kg
Final enthalpy	4182	J/kg
Initial entropy	4182	J/kg·K
Final entropy	4182	J/kg·K
Initial internal energy	4182	J/kg
Final internal energy	4182	J/kg
Initial Gibbs free energy	4182	J/kg
Final Gibbs free energy	4182	J/kg
Initial Helmholtz free energy	4182	J/kg
Final Helmholtz free energy	4182	J/kg
Initial chemical potential	4182	J/kg
Final chemical potential	4182	J/kg
Initial activity	1.0	
Final activity	1.0	
Initial fugacity	1.0	bar
Final fugacity	1.0	bar
Initial vapor pressure	1.013	bar
Final vapor pressure	1.013	bar
Initial saturation temperature	100	°C
Final saturation temperature	100	°C
Initial saturation pressure	1.013	bar
Final saturation pressure	1.013	bar
Initial critical temperature	374	°C
Final critical temperature	374	°C
Initial critical pressure	221	bar
Final critical pressure	221	bar
Initial critical density	322	kg/m³
Final critical density	322	kg/m³
Initial critical viscosity	0.001	Pa·s
Final critical viscosity	0.001	Pa·s
Initial critical thermal conductivity	0.6	W/m·K
Final critical thermal conductivity	0.6	W/m·K
Initial critical specific heat capacity	4182	J/kg·K
Final critical specific heat capacity	4182	J/kg·K
Initial critical enthalpy	4182	J/kg
Final critical enthalpy	4182	J/kg
Initial critical entropy	4182	J/kg·K
Final critical entropy	4182	J/kg·K
Initial critical internal energy	4182	J/kg
Final critical internal energy	4182	J/kg
Initial critical Gibbs free energy	4182	J/kg
Final critical Gibbs free energy	4182	J/kg
Initial critical Helmholtz free energy	4182	J/kg
Final critical Helmholtz free energy	4182	J/kg
Initial critical chemical potential	4182	J/kg
Final critical chemical potential	4182	J/kg
Initial critical activity	1.0	
Final critical activity	1.0	
Initial critical fugacity	1.0	bar
Final critical fugacity	1.0	bar
Initial critical vapor pressure	1.013	bar
Final critical vapor pressure	1.013	bar
Initial critical saturation temperature	100	°C
Final critical saturation temperature	100	°C
Initial critical saturation pressure	1.013	bar
Final critical saturation pressure	1.013	bar
Initial critical critical temperature	374	°C
Final critical critical temperature	374	°C
Initial critical critical pressure	221	bar
Final critical critical pressure	221	bar
Initial critical critical density	322	kg/m³
Final critical critical density	322	kg/m³
Initial critical critical viscosity	0.001	Pa·s
Final critical critical viscosity	0.001	Pa·s
Initial critical critical thermal conductivity	0.6	W/m·K
Final critical critical thermal conductivity	0.6	W/m·K
Initial critical critical specific heat capacity	4182	J/kg·K
Final critical critical specific heat capacity	4182	J/kg·K
Initial critical critical enthalpy	4182	J/kg
Final critical critical enthalpy	4182	J/kg
Initial critical critical entropy	4182	J/kg·K
Final critical critical entropy	4182	J/kg·K
Initial critical critical internal energy	4182	J/kg
Final critical critical internal energy	4182	J/kg
Initial critical critical Gibbs free energy	4182	J/kg
Final critical critical Gibbs free energy	4182	J/kg
Initial critical critical Helmholtz free energy	4182	J/kg
Final critical critical Helmholtz free energy	4182	J/kg
Initial critical critical chemical potential	4182	J/kg
Final critical critical chemical potential	4182	J/kg
Initial critical critical activity	1.0	
Final critical critical activity	1.0	
Initial critical critical fugacity	1.0	bar
Final critical critical fugacity	1.0	bar
Initial critical critical vapor pressure	1.013	bar
Final critical critical vapor pressure	1.013	bar
Initial critical critical saturation temperature	100	°C
Final critical critical saturation temperature	100	°C
Initial critical critical saturation pressure	1.013	bar
Final critical critical saturation pressure	1.013	bar
Initial critical critical critical temperature	374	°C
Final critical critical critical temperature	374	°C
Initial critical critical critical pressure	221	bar
Final critical critical critical pressure	221	bar
Initial critical critical critical density	322	kg/m³
Final critical critical critical density	322	kg/m³
Initial critical critical critical viscosity	0.001	Pa·s
Final critical critical critical viscosity	0.001	Pa·s
Initial critical critical critical thermal conductivity	0.6	W/m·K
Final critical critical critical thermal conductivity	0.6	W/m·K
Initial critical critical critical specific heat capacity	4182	J/kg·K

CORRESPONDENCE INFORMATION

APPLICATION INFORMATION

Total Drawing Sheets:: 15
Formal Drawings?: Yes
Application Type:: Utility
Docket Number:: 35.C15484
Secrecy Order in Parent Appl.?: No

Representative Customer Number:: 5514

Foreign Application One:: 193340/2000
Filing Date:: 06-27-2000
Country:: Japan
Priority Claimed:: Yes